

# Horsepower Selection Guide - Maximum Square Footage

## FOR SECTIONAL DOORS - TYPE:

MODEL	H.P.	Steel:	Steel:	Steel:	Steel:	
		Fiber- glass	-24GA -22 GA	-20GA -24 GA	16GA 20 GA	.16GA Insu- lated
		Alumi- num	Insul. Wood	Insu- lated		
LT,LJ,LH	1/2	350	310	240	210	165
T,J,H	1/3	270	260	200	200	150
T,J,H	1/2	360	325	260	230	180
T,J,H	3/4	480	450	400	310	230
T,J	1	585	540	490	380	280
APT	1/2	350	320	240	220	170
APT	3/4	470	440	320	300	220
GT	1/2	400	350	320	250	200
GT	3/4	560	500	450	420	250
GT	1	625	575	520	500	300
CGH	1/2	375	340	270	240	185
CGH	3/4	500	470	415	320	240
CGH	1	610	560	510	405	290

**FOR ROLLING DOORS AND GRILLES - TYPE**

<b>MODEL</b>	<b>H.P.</b>	24 GA	22 GA	20 GA	18 GA	Insu-	Steel	Aluminum	Steel	Aluminum
		Steel Rolling	Rolling Shutter	Steel Rolling	Steel Rolling	lated Rolling	Rolling Grille	Rolling Grille	Counter Shutter	Counter Shutter
<b>LJ, LH</b>	<b>1/2</b>	190	165	150	-	-	180	210	165	210
<b>SJ</b>	<b>1/2</b>	-	-	-	-	-	120	140	100	135
<b>G,J</b>	<b>1/2</b>	135	125	120	-	-	135	160	125	140
<b>H,J</b>	<b>1/3</b>	210	190	175	130	100	210	265	190	220
<b>H,J</b>	<b>1/2</b>	275	250	225	170	130	260	350	250	-
<b>H,J</b>	<b>3/4</b>	340	310	290	215	165	340	450	-	-
<b>MG</b>	<b>1/2</b>	290	260	240	190	160	280	400	-	-
<b>MG</b>	<b>3/4</b>	370	320	300	240	180	375	550	-	-
<b>MG</b>	<b>1</b>	440	360	340	270	200	480	640	-	-
<b>MG</b>	<b>1 1/2</b>	-	460	430	360	260	620	-	-	-
<b>MG</b>	<b>2</b>	-	-	560	480	350	-	-	-	-
<b>MG</b>	<b>3</b>	-	-	840	700	520	-	-	-	-
<b>MG</b>	<b>5</b>	-	-	1200	920	780	-	-	-	-